CB7

## MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SELF LEVELING UNDERLAYMENT LATEX PRIMER HMIS CODES: H F R P PRODUCT CODE: 3020.ALT SECTION I - MANUFACTURER IDENTIFICATION EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846

DATE REVISED : 07-24-99 NAME OF DREDADED : CONTINUE SECTION 1882-0846 SECTION II - INGREDIENTS/SARA III INFORMATION OCCUPATIONAL EXPOSURE VAPOR PRESSURE Wt. CAS NUMBER OSHA PEL ACGIH TLV mm Hg @ TEMP % COMPONENTS Water ăăăăăăăãããããããããããããããããã Acrylic Polymer N/A \* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\* SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS 1.0 SPECIFIC GRAVITY (H2O=1): BOILING RANGE: N/A EVAPORATION RATE: SLOWER THAN ETHER VAPOR DENSITY: HEAVIER THAN AIR SOLUBILITY IN WATER: EMULSION APPEARANCE AND ODOR: MILKY WHITE LIQUID EMULSION SECTION IV - FIRE AND EXPLOSION HAZARD DATA FLASH POINT: N/A FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A EXTINGUISHING MEDIA: , WATER FOG SPECIAL FIREFIGHTING PROCEDURES NONE UNUSUAL FIRE AND EXPLOSION HAZARDS DRIED FILM IS COMBUSTIBLE SIMILAR TO WOOD. BURNING DRY RESINS EMITS DENSE, BLACK SMOKE. PAGE 2 OF 3 MATERIAL SAFETY DATA SHEET 3020.ALT EXTERNAL BENEFIT SECTION V - REACTIVITY DATA SECRET-SECTION V -STABILITY: STABLE CONDITIONS TO AVOID NONE

INCOMPATIBILITY (MATERIALS TO AVOID) ADDITION OF CHEMICALS MAY CAUSE COAGULATION.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS IF BURNED, PRODUCES CARBON MONOXIDE AND HYDROCARBONS.

## IMsdsDataSheetDisplay

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA -----

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE NO ADVERSE EFFECTS ARE ANTICIPATED.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE SKIN: PROLONGED OR REPEATED MAY CAUSE IRRITATION. EYE: MAY CAUSE SLIGHT EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE ABSORPTION THRU SKIN IS UNLIKELY DUE TO PHYSICAL PROPERTIES OF EMULSION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE SINGLE DOSE ORAL TOXICITY IS LOW.

HEALTH HAZARDS (ACUTE AND CHRONIC) NO SPECIFIC DATA AVAILABLE, HOWEVER, REPEATED EXPOSURES ARE NOT ANTICIPATED TO CAUSE ANY SIGNIFICANT ADVERSE PROBLEMS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO NOT LISTED BY NTP, IARC, OR OSHA AS CONTAINING CARCINOGENS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE NONE

EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: IRRIGATE IMMEDIATELY WITH WATER FOR AT LEAST 5 MINUTES.
SKIN CONTACT: WASH OFF WITH SOAP AND WATER.
INHALED: NO ADVERSE EFFECTS ANTICIPATED.
SWALLOWED: NO ADVERSE EFFECTS ANTICIPATED.

3020.ALT MATERIAL SAFETY DATA SHEET

PAGE 3 OF 3

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED FLUSH AREA WITH WATER IMMEDIATELY. AVOID UNNECESSARY EXPOSURE AND CONTACT.

WASTE DISPOSAL METHOD
DO NOT FLUSH INTO SEWERS. CAPTURE SPILLS AND BURY IN AN APPROVED LAND FILL OR
BURN SOLID WASTES IN ADEQUATE INCENERATOR.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE AT TEMPERATURES BETWEEN 40 DEGREES F AND 110 DEGREES F.

OTHER PRECAUTIONS

SECTION VIII - CONTROL MEASURES -----

RESPIRATORY PROTECTION FOR MOST CONDITIONS, NO RESPIRATORY PROTECTION SHOULD BE NEEDED, HOWEVER, IN MISTY ATMOSPHERES USE APPROVED MIST RESPIRATOR.

VENTILATION NORMAL VENTILATION IS ADEQUATE.

PROTECTIVE GLOVES CHEMICAL RESISTANT GLOVES ARE RECOMMENDED.

EYE PROTECTION

USE SAFETY GLASSES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT WEAR CLEAN, LONG SLEEVED, BODY COVERING CLOTHING.

WORK/HYGIENIC PRACTICES SHOULD BE ENFORCED.

SECTION IX - DISCHAIMER ----

DISCLAIMER
THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT
WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE
ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT,
APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.